

ECO PL ANTI-MIGRATION BASE

It is a phthalate free and plastisol free barrier prints.

Highlights

- ▶ It has high wash resistance.
- ▶ It is used to prevent that appears on the surface of remained sublimated and reactive colorants on thermal process.
- ▶ It doesn't contain Phthalate and PVC. Suitable to ecological standards.
- ▶ It is used as a barrier for doesn't pass surface of pigments.
- ▶ It provides to elastic and excellent dye barrier on dark colored.

Printing Tips

- ▶ It has been manufactured for barrier prints.

Compliance

- ▶ Suitable to ecological standards.
- ▶ For Ecological Certifications, please visit www.inknovators.com

Precautions

- ▶ After using, the screen should be cleaned with synthetic thinner or plastisol screen opener.
- ▶ It is packed in 10kg cans.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: info@inknovators.com

Fabric Types

Works on polyester or polyester blend fabrics



Mesh

Counts: 55-61 mesh




Squeegee

Durometer: 60-80 Shore V type dr. blade



Cure Temperatures

320°F(160°C) for 1.5 minutes



Additives

Do not use any additives that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Synthetic Thinner or Plastisol Screen Opener



Health & Safety

Please see: Safety Data Sheet

