



HYBRID CRACK CLEAR BASE

Product Information Bulletin

Recommended Parameters

HYBRID CRACK CLEAR BASE

It is a water based printing base used to achieve a cracking effect in textile printing. It can be used as a transparent or can be coloured with pigments

Highlights

- ▶ It is provide easily to use during printings
- ▶ If under the advised conditions is fixed, wash fastness is high
- ▶ The best vivid colors in cracking effect
- ▶ Washing tests should be applied 24 hours after fixing

Printing Tips

- ▶ It has been manufactured for the products which don't want to take foil print

Compliance

- ▶ Suitable to ecological standards.

Precautions

- ▶ Never use water to reduce the viscosity.
- ▶ Before usage, please stir the product well. Do not use any additives that are not advised.
- ▶ After using, the screen should be cleaned with water
- ▶ Soluble in water.
- ▶ It is packed in 30kg and 60kg blue polyethylene cans.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: info@inknovators.com

Mesh

Counts: 34-43 mesh



Squeegee

Durometer: 50-60
Shore U type dr. blade



Cure Temperatures

320°F(160°C) for 1.5 minutes
280°F(140°C) for 2 minutes



Additives

Do not use any additives that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Use only water



Health & Safety

Please see: Safety Data Sheet

