



HYBRID LM CLEAR BASE

Product Information Bulletin

Recommended Parameters

HYBRID LM CLEAR BASE

Water-based printing base used to achieve an elastic and soft touching effect in textile printing. It can be used as a transparent or can be coloured with pigments.

Highlights

- If used correctly as advised, the dry-wet rubbing and washing fastness are high
- Elastic and soft-handfeel clear for open mesh.
- It provides elastic and soft touch prints.
- Rubbing and washing tests should be applied 24 hours after curing

Printing Tips

- It has been manufactured for elastic and proper surface printings.
- According to request, all water based pastes are colored with this product.
- If it is used 5% and above, wet&dry rubbing can be damaged.

Compliance

- Suitable to ecological standards.
- For Ecological Certifications, please visit www.inknovators.com

Precautions

- Never use water to reduce the viscosity.
- Before usage, please stir the product well. Do not use any additives that are not advised.
- After using, the screen should be cleaned with water and sponge.
- Soluble in water.
- It is packed in 30kg and 60kg blue polyethylene cans.
- It can be mixed with Hybrid LM White in any ratio.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

Mesh

Counts: 43-62 mesh



Squeegee

Durometer: 55-60 Shore
U type dr. blade



Cure Temperatures

320°F(160°C) for 1.5 minutes
280°F(140°C) for 2 minutes



Additives

Do not use any additives
that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Water and sponge



Health & Safety

Please see: Safety Data Sheet

