



HYBRID WT WHITE

Product Information Bulletin

Recommended Parameters

HYBRID WT WHITE

It is a water base printing paste where used to achieve an elastic,soft touching and white covering effect in textile printing. Does not dry during the print and block the screen.

Highlights

- If used correctly as advised, it does not dry during the print and block in the silk-screen.
- Hybrid WT White has extremely wash fastness.
- Rubbing and washing tests should be applied 24 hours after curing.
- Elastic and soft texture effect with excellent coverage
- Needs to be printed as a base white

Printing Tips

- It has been manufactured for wet on wet printing process.

Compliance

- Suitable to ecological standards.

Precautions

- It can be mixed with Hybrid WT Clear Base in any ratio.
- Before usage, please stir the product well. Do not use any additives that are not advised.
- After using, the screen should be cleaned with water and sponge.
- Soluble in water.
- It is packed in 30kg and 60kg blue polyethylene cans.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

Mesh

Counts: 43-55 mesh



Squeegee

Durometer: 50-60 Shore
U type dr. blade



Cure Temperatures

280°F(140°C) for 2 minutes



Additives

Do not use any additives
that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Water and sponge



Health & Safety

Please see: Safety Data Sheet



HYBRID WT WHITE