

PL FLU BLUE

Product Information Bulletin

PL FLU BLUE

It is a phthalate free plastisol based printing base used to achieve fluorescent coloured printing effect with elastic, covering and soft touching features in textile printing

🛄 Highlights

- Matt, elastic and soft-handfeel plastisol colors.
- It is phthalate free. However, it is not suitable to ecological standards due to containing PVC.
- It is easily fixed.
- Available colors black, white, yellow, green, blue, red, orange and more.
- It allows which turns the requested color of printing paste.

Printing Tips

It has been manufactured for plastisol fluorescent colors

It is not suitable to ecological standards due to containing PVC.

Precautions

- Before usage, please stir the product well. Do not use any additives that are not advised.
- After using, the screen should be cleaned with synthetic thinner or plastisol screen opener.
- It is packed in 10kg cans.
- It can be mixed with PL Clear Base and PL White.
- Fluorescent colors can be mixed with any PL Inknovators inks.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

Recommended Parameters

Squeegee

Mesh

Durometer: 60-80 Shore V type dr. blade

Counts: 43-120 mest



Cure Temperatures 320°F(160°C) for 1.5 minutes



Additives

Do not use any additives that are not advised In order to reduce the viscosity, PL

| ſ | | | 1 |
|---|--------------|---|---|
| | /2 | - | |
| | \mathbb{Z} | | |
| U | ۵ | | |

Reducer can be added 3% into it

| | | 6 | _ | |
|---|---|---|---|--|
| ſ | 2 | | | |

Shipping & Storage 41°F - 86°F (5°C - 30°C)



Clean Up

Synthetic Thinner or Plastisol Screen Opener



Health & Safety Please see: Safety Data Sheet



FLU BLUE

Ч

DAF Kimva İc ve Dıs Tic. A.S. Taşocağı Caddesi No:3 Ağaoğlu My Office 212 No:75 34218, Mahmutbey / Istanbul-TURKEY