

PL MATT AGENT

Product Information Bulletin

Recommended Parameters

PL MATT AGENT

It is a phthalate free mattifying

Highlights

- Lt provides mattifying appearance of PL Series.
- Lt is used to obtain surface of puffed suede effect.
- Washing test should be applied 24 hours after curing.

Printing Tips

- It has been manufactured for matt appearance to PL products.
- Recommended percentage: between %1-10
 Before use, please stir the ink well. After using, the screen should be cleaned with the synthetic thinner.

Compliance

It is not suitable to ecological standards because it contains PVC.

Precautions

- It is packed in 1kg, 5kg, 10kg, 20kg, 25kg, 30kg and 60kg plastic cans.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ► In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ► Email: info@inknovators.com







Shipping & Storage 41°F - 86°F (5°C - 30°C)



Health & Safety
Please see: Safety Data Sheet

