

PL THICKENER

Product Information Bulletin

PL THICKENER

It is a phthalate free thickener in textile printing.

Highlights

- It viscosity capability is perfect even if small quantities therefore it should be tried in pastes.
- It protects to alive of pigments.
- It provides to raise of viscosity of print paste and liquids which has pH 7 and above
- It provides excellent increase of viscosity of PL products.

Shipping & Storage 41°F - 86°F (5°C - 30°C)

Recommended Parameters



Precautions

- Before usage, please stir the product well. Do not use any additives that are not advised.
- After using, the silk-screen should be cleaned with organic solvent.
- Because the thickening effect of the PL Thickener is very high, it is recommended to use it as a trial.
- It is packed in 5kg, 30kg, 60kg and 120kg plastic cans.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

Health & Safety Please see: Safety Data Sheet



DAF Kimya İç ve Dış Tic. A.Ş.

TDS No:183