

### PU Transfer Opaque Clear

PU Transfer Opaque Clear, for water-based textile printing applications, to obtain a covering printing effect. In textile printing applications, it can be used as transparent or colored with water-based pigments.

#### Highlights

- If used correctly as advised, the dry-wet rubbing and washing fastness are high
- Elastic and soft-handfeel clear for open mesh.
- It provides elastic and soft touch prints.
- Rubbing and washing tests should be applied 24 hours after curing

#### Printing Tips

- It has been manufactured for elastic and proper surface printings.

#### Compliance

- Suitable to ecological standards.
- For Ecological Certifications, please visit [www.inknovators.com](http://www.inknovators.com)

#### Precautions

- Never use water to reduce the viscosity.
  - Before usage, please stir the product well. Do not use any additives that are not advised.
  - After using, the screen should be cleaned with water and sponge.
  - Soluble in water.
  - It is packed in 5kg, 10kg, 20kg, 30kg and 60kg blue polyethylene cans.
  - It can be mixed with PU Transfer White in any ratio.
  - The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
  - In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
  - The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: [info@inknovators.com](mailto:info@inknovators.com)

#### Mesh

Counts: 43-62 mesh




#### Squeegee

Durometer: 55-60 Shore  
U type dr. blade



#### Cure Temperatures

320°F(160°C) for 1.5 minutes  
280°F(140°C) for 2 minutes



#### Additives

Do not use any additives that are not advised



#### Shipping & Storage

41°F - 86°F (5°C - 30°C)



#### Clean Up

Water and sponge



#### Health & Safety

Please see: Safety Data Sheet

