



PU TRANSFER WHITE

Product Information Bulletin

Recommended Parameters

PU TRANSFER WHITE

Polyurethane based elastic white, used to achieve an elastic, soft touching and white covering effect in transfer printing.
Does not dry during the print and does not block the screen.

Highlights

- ▶ If used correctly as advised, it does not during the print and block in the silk-screen
- ▶ Elastic and soft texture effect with excellent coverage.
- ▶ It has extremely wash fastness.
- ▶ Rubbing and washing tests should be applied 24 hours after curing

Printing Tips

- ▶ It has been manufactured for elastic and proper surface printings.
- ▶ According to request, all water based pastes can be colored with this product.

Compliance

- ▶ Suitable to ecological standards.
- ▶ For Ecological Certifications, please visit www.inknovators.com

Precautions

- ▶ Before usage, please stir the product well. Do not use any additives that are not advised.
- ▶ After using, the screen should be cleaned with water and sponge.
- ▶ Soluble in water.
- ▶ It is packed in 5kg, 10kg, 20kg, 30kg and 60kg blue polyethylene cans.
- ▶ It can be mixed with PU Clear Base in any ratio.
- ▶ The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- ▶ In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- ▶ The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any nonconforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ▶ Email: info@inknovators.com

Mesh

Counts: 43-62 mesh



Squeegee

Durometer: 55-60 Shore
U type dr. blade



Cure Temperatures

320°F (160°C) , 1,5 mins



Additives

Do not use any additives
that are not advised



Shipping & Storage

41°F - 86°F (5°C - 30°C)



Clean Up

Water and sponge



Health & Safety

Please see: Safety Data Sheet

