inknovators

Recommended Parameters

PRINTING BASE 2

It is a water based printing base used to achieve soft touching effect in textile printing. It is colored with pigments.

Highlights

- If used correctly as advised, it has extremely wash strenght and fastness
- It provides to elastic and soft touch prints
- Vivid Colors and soft-handfeel effects for light color garments

Printing Tips

- It has been manufactured on light base for elastic and proper surface printings

Compliance

- Suitable to ecological standards.
- For Ecological Certifications, please visit www.inknovators.com

⚠ Precautions

- Never use water to reduce the viscosity.
- Before usage, please stir the product well. Do not use any additives that are not advised.
- After using, the screen should be cleaned with water and sponge.
- Soluble in water.
- It is packed in 30kg and 60kg blue polyethylene cans.
- It can be mixed with Hybrid LM, Hybrid HM, Hybrid 2 HM and Hybrid 3 HM series in any ratio.
- The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. If any further help or assistance is required, our technical department is ready for help.
- In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- Email: info@inknovators.com

Mesh
Counts: 77-120 mesh

Squeegee
Durometer: 50-60
Shore U type dr. blade

Cure Temperatures
320°F(160°C) for 1.5 minutes
280°F(140°C) for 2 minutes

Additives
Do not use any additives that are not advised

Shipping & Storage
41°F - 86°F (5°C - 30°C)

Clean Up
Water and sponge

Health & Safety
Please see: Safety Data Sheet

PRINTING BASE 2