

## Hybrid TB Clear Base

### General

Elastic and soft texture self curable ink for table printing without any additives. Please make the wash tests after 48 hours and please do not stretch the print before washing process. Hybrid TB Clear Base increases color yield when used together with Hybrid TB Clear Base.

### Advantages

Hybrid TB Clear Base provides :

- Excellent softness
- Non-tacky surface
- Curing at room temperature
- Extra elasticity
- If used correctly as advised, the dry-wet rubbing and washing fastness are high.
- It provides high light fastness and wash fastness.
- High color efficiency is available with TB Clear.
- Self curable in 48 hours

### Applications & Usage

- Hybrid TB Clear Base is used for coloration of textile printing dyes.
- According to request, all water based pastes are colored with this product
- Do not use any additives that are not advised.
- It provides to print with the silk-screen that are made between 43-55 mesh.
- 55-60 Shore, U type dr blade should be used.
- Before use please stir this product well.

### Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C of temperature.
- It should be consumed within 2 years after the production date.

## Technical Details



### Appearance

Pasta



### Odor

Characteristic



### Color

Yellowish



### Viscosity

[(77°F/25°C) sp:7,rpm:20 Brookfield] :  
80.000 – 90.000 [mPa.s]



### Density

1,1 g/cm<sup>3</sup> (25 °C/77 °F)



### pH

7,5 – 8,5



### Boiling Point

>100°C (212°F)



### Solubility

Soluble with water

### Explosion Hazard

It is not explosive



### Packaging Information

Hybrid TB Clear Base is packed in  
1/5/10/20/30 kg blue polyethylene  
cans

## Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help. Printing performance and the quality may change with different company and application conditions. So please begin your printings serial process after completing your own trial tests.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.

Rev. DATE: 28 January 2026

Rev. No: 00

**ALV KİMYA SANAYİ İÇ VE DIŞ TİCARET ANONİM ŞİRKETİ**

Velimeşe OSB Mah. 2.Yanyol Cad.No:12 Ergene / TEKİRDAĞ

+90 282 676 42 05 [info@alvkimya.com](mailto:info@alvkimya.com)

TDS No: 015 Page 1/1