

Hybrid TB White

General

Hybrid TB White is a self curable, elastic white for table printing. Washing test should be done 24 hours after printing. Please do not stretch before 24 hours.

Advantages

It provides

- Excellent coverage
- Curing at room temperature
- Low curing
- Excellent opacity
- Suitable to ecological standards.

Applications & Usage

- Hybrid TB White has been manufactured for elastic and proper surface printings.
- It can be mixed with Hybrid TB White in any ratio.
- Do not use any additives that are not advised.
- It provides to print with the silk-screen that are made between
- 43-55 mesh. 60 – 70 Shore, U type should be used.
- After using, the silk-screen should be cleaned with water.
- Rubbing and washing tests should be applied 48 hours after curing.
- Before use, please stir the product well.

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place between (+5)-(+30)°C of temperature.
- It should be consumed within 2 years after the production date.

Technical Details



Appearance

Pasta



Odor

Characteristic



Color

White



Viscosity

[(77°F/25°C) sp:7,rpm:20 Brookfield] :
85.000 – 100.000 [mPa.s]



Density

1,32 g/cm³ (25 °C/77 °F)



pH

8,0 – 8,5



Boiling Point

>100°C (212°F)



Solubility

Soluble with water

Explosion Hazard

It is not explosive



Packaging Information

Hybrid TB White is packed in
1/5/10/20/30 kg blue polyethylene
cans

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help. Printing performance and the quality may change with different company and application conditions. So please begin your printings serial process after completing your own trial tests.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.

Rev. DATE: 28 January 2026

Rev. No: 00

ALV KİMYA SANAYİ İÇ VE DIŞ TİCARET ANONİM ŞİRKETİ

Velimeşe OSB Mah. 2.Yanyol Cad.No:12 Ergene / TEKİRDAĞ

+90 282 676 42 05 info@alvkimya.com

TDS No: 016 Page 1/1