

Hybrid Antimigration Base

General

A water based anti-migration base for polyester or fabrics contain polyester at different ratios.

Advantages

- Very good effect for polyester and sublimation fabrics
- prevents migration
- high performance
- Extra Barrier Paste is prevent to contaminate base color's to print.
- Especially Extra Barrier Paste effective on polyester fabric and reactive printing fabric. Extra Barrier Paste has extremely wash fastness.

Applications & Usage

- Hybrid Antimigration Base is used for prevent to contaminate prints of polyester fabric & reactive printing fabric.
- Curing temperature : 160°C(320°F), 1 min 30 seconds ; 140°C(284°F), 2 mins.
- Suitable to ecological standards.
- Before use, please stir Hybrid Antimigration Base well.
- Do not use any additives that are not advised.
- It provides to print with the silk-screen that are made between 43-55 mesh.
- It can be fixed under room temperature.
- 50-70 Shore, U type should used

Storage & Shelf Life

- Keep containers dry and tightly closed. Store in a ventilated place at room temperature.
- It should be consumed within 2 years after the production date.

Technical Details



Appearance

Pasta



Odor

Characteristic



Color

Grey



Viscosity

[(77°F/25°C) sp:7,rpm:20 Brookfield] :
80.000 – 90.000 [mPa.s]



Density

1,27 g/cm³ (25 °C/77 °F)



pH

8,0 – 9,0



Boiling Point

>100°C (212°F)



Solubility

Soluble with water



Explosion Hazard

It is not explosive



Packaging Information

Hybrid Antimigration Base is packed in 1/5/10/20/30 kg blue polyethylene cans

Important

The technical application and information that have been given above, are designed only as using instructions. Should not be considered as a warranty for any other use. When any help or assistance is required, our technical department is ready for help. Printing performance and the quality may change with different company and application conditions. So please begin your printings serial process after completing your own trial tests.

In case of emergency, Safety Data Sheet of this product should be ready for help at the working area. The warnings are given on safety data sheet of this product is for use outside the manufacturer/ distributor to direct/indirect can not be held responsible for any loss or damage.

Rev. DATE: 28 January 2026

Rev. No: 00

ALV KİMYA SANAYİ İÇ VE DIŞ TİCARET ANONİM ŞİRKETİ

Velimeşe OSB Mah. 2.Yanyol Cad.No:12 Ergene / TEKİRDAĞ

+90 282 676 42 05 info@alvkimya.com

TDS No: 019 Page 1/1