

TABLE ADHESIVE

Product Information Bulletin

TABLE ADHESIVE

It is waterbased table adhesive.

Highlights

- Lt has improved drying properties which are peeling, adhesion and cutting.
- ► It is used for gluing textile materials to print tables.
- It is economical than sprays.
- ► It provides excellent adhesion even if high application speed.

Printing Tips

- It designed to strength for pressure of low noise that is emulsion polymer for ready-to-use.
- It sprays to application frames with special air spray aparatus.
 It has low water strength therefore Table Adhesive can be used with warehouse labels that should be designed as hard and/or plastise (made from PVS, PE and PP film)

Precautions

- ► Before usage, please stir the product well.
- Filtration should be advised with low power pump (>50μ)
- It is packed in 30 kg plastic cans.
- The technical application and information that have been given above, are designed only as using
 instructions. Should not be considered as a warranty for any other use. If any further help or
 assistance is required, our technical department is ready for help.
- ► In case of emergency, Safety Data Sheet of this product should be ready for help at the working area.
- The warnings available on safety data sheets have been written for the purpose of providing comprehensive information on the products & in case of any noncomforming usage can not be held responsible for any direct and/or indirect loss or damage of the manufacturer/distributor.
- ► Email: info@inknovators.com

Recommended Parameters

Physical and Chemical Properties



Appearance: Milky, Liquid

Viscosity: max. 600 mPas

Density: 1,05 g/cm³

pH: 7.0-8.0

Boiling Point: >212°F

Solid content % : 60±1

Additives



Do not use any additives that are not advised

Shipping & Storage



41°F - 86°F (5°C - 30°C)





Please see: Safety Data Sheet

TDS No: 068